

LED FLOOD LIGHT

LED FLOOD LIGHT



High efficient LED flood light suitable for outdoor and indoor area lighting. Body made of die-cast aluminum, black powder coated with toughened glass. With high quality SMD chips. Save up 80% energy have better lighting characteristics than traditional metal halide.

Features:

Slim & Compact design, Instant start, No flickering

High strength and impact resistance

Life span: 30,000 hrs

IP 65

Working temp: -40°C to 60°C

Model No.	Watts Efficiency	Voltage	Luminous	Color Temp	CRI	IP Rating	Power factor	Beam Angle (Hrs)	Lifetime Materials	Housing
KB-TG-D-30W	30W	85-265V	≥100LM/W	6500K	≥70	IP65	0.9	120°	30,000	Aluminum
KB-TG-D-50W	50W	85-265V	≥100LM/W	6500K	≥70	IP65	0.9	120°	30,000	Aluminum
KB-TG-D-100W	100W	85-265V	≥100LM/W	6500K	≥70	IP65	0.9	120°	30,000	Aluminum
KB-TG-D-150W	150W	85-265V	≥100LM/W	6500K	≥70	IP65	0.9	120°	30,000	Aluminum
KB-TG-D-200W	200W	85-265V	≥100LM/W	6500K	≥70	IP65	0.9	120°	30,000	Aluminum